




Model: 9HD7M

9 Inch Monitor Metal

This 9 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 9 inch monitor has a sturdy metal housing and is ideal for desktop, flush and wall mounting. The 9HD7M can be connected via HDMI, VGA, BNC or RCA connections.

- ✓ 1920 x 1200 resolution (Full HD)
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Flush, embedded, wall, desktop
- ✓ External dimensions: 8.6 x 5.9 x 1.4 inches



General

Manufacturer	Beetronics
Item Number	9HD7M
Previous Model	9HDM
Product Name	9 Inch Monitor Metal
Warranty	2 Years
User Manual	Download PDF
Quickstart	Download PDF

Panel

Diagonal Size	9.0 Inches (228 mm)
Panel Type	IPS-LCD
Aspect Ratio	16:10 (16:9, 4:3 Adjustable)
Response Time	10 ms
MTBF	50K
Native Resolution	1920 x 1200
Supported Resolutions	1920 x 1200 (max), 640 x 480 (min)
Pixels Per Inch	254 PPI
Backlight	LED
Brightness	450 cd/m2
Contrast	900:1
Viewing Angle	178° Horizontal, 178° Vertical

Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA Video	1x
USB-A	1x Integrated USB Media Player
AUX Input (3.5mm)	1x
AUX Output (3.5 mm)	1x

Size & Weight

Colour	Black
Dimensions (Without Stand)	8.6 x 5.9 x 1.4 Inches
Image Size	7.6 x 4.8 Inches
Weight	2.0 lbs (2.9 lbs With Stand)

Features & Functions

Audio	Integrated Speakers
Key-Lock	The control buttons can be blocked.
Auto-On	Automatically powers on when it receives current or a signal.
Dimmable	Adjustable Backlight Brightness
Mirroring	Teleprompter compatible. Image can be horizontally and vertically mirrored.
Orientation	Landscape, Portrait, Face-up
USB Media Player	The monitor is equipped with a built-in USB media player.

Power

Input Voltage	DC 9-33V
Consumption	Typical 7.7 W (On), 0.4 W (Standby)
Power Supply	External DC (Power Adapter Included)
Power Adapter	Input: AC100-240V, 50/60Hz , Output: 12V-2A
Power Adapter Output Connector	DC Barrel Plug 2.1mm x 5.5mm

Environmental

Max. Non-Stop Operating Time	24/7
Operating Temperature	-4°F to +140°F
Storage Temperature	-4°F to +158°F
Operating Humidity	20% - 85% Non-Condensing

Mounting

Wall Mount	✔ VESA 75x75mm
Flush Mount	✔ Mounting Strips Included
Stand	✔ Adjustable and Detachable

Certifications & Standards

Certifications	CE, FCC, RoHS, REACH, WEEE, IC, C-Tick, UKCA, e-Mark, EN50155, EN60601-1-1, EN60601-1-2, CCC
----------------	--

Package Content

Includes	Monitor, Stand, Remote Control, Mounting Strips, AC Power Adapter, Manual
----------	---

Compatible Accessories

Dimmer	Compatible With External Dimmer (DMK7/DMK8)
Rack Mounting	Compatible With 19 Inch Rack Mount Kit (RMK2)
Wall Mounting	Compatible With Flat Wall Mount Bracket (VWB1)
Stand	VDK3 Included as Standard



