




Model: 22HD7M

## 22 Inch Monitor Metal

This 22 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 22 inch monitor has a sturdy metal housing and is ideal for desktop, flush and wall mounting. The 22HD7M can be connected via HDMI, VGA, BNC or RCA connections.

- ✓ 1920 x 1080 resolution (Full HD)
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Flush, embedded, wall, desktop
- ✓ External dimensions: 20.1 x 12.1 x 1.6 inches



## General

Manufacturer	Beetronics
Item Number	22HD7M
Previous Model	22HDM
Product Name	22 Inch Monitor Metal
Warranty	2 Years
User Manual	<a href="#">Download PDF</a>
Quickstart	<a href="#">Download PDF</a>

## Panel

Diagonal Size	21.6 Inches (549 mm)
Panel Type	IPS-LCD
Aspect Ratio	16:9 (4:3 Adjustable)
Response Time	10 ms
MTBF	50K
Native Resolution	1920 x 1080
Supported Resolutions	1920 x 1080 (max), 640 x 480 (min)
Pixels Per Inch	102 PPI
Backlight	LED
Brightness	300 cd/m2
Contrast	3000:1
Colour Encoding System	PAL/NTSC/SECAM
Viewing Angle	178° Horizontal, 178° Vertical

## Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA Video	1x
USB-A	1x Integrated USB Media Player
AUX Input (3.5mm)	1x
AUX Output (3.5 mm)	1x

## Size & Weight

Colour	Black
Dimensions (Without Stand)	20.1 x 12.1 x 1.6 Inches
Image Size	18.8 x 10.6 Inches
Weight	9.5 lbs (11.5 lbs With Stand)

## Features & Functions

Audio	Integrated Speakers
Key-Lock	The control buttons can be blocked.
Auto-On	Automatically powers on when it receives current or a signal.
Dimmable	Adjustable Backlight Brightness
Mirroring	Teleprompter compatible. Image can be horizontally and vertically mirrored.
Orientation	Landscape, Portrait, Face-up
USB Media Player	The monitor is equipped with a built-in USB media player.

## Power

Input Voltage	DC 9-36V
Consumption	Typical 20.0 W (On), 0.4 W (Standby)
Power Supply	External DC (Power Adapter Included)
Power Adapter	Input: AC100-240V, 50/60Hz , Output: 19V-1.5A
Power Adapter Output Connector	DC Barrel Plug 2.1mm x 5.5mm

## Environmental

Max. Non-Stop Operating Time	24/7
Operating Temperature	-4°F to +140°F
Storage Temperature	-4°F to +158°F
Operating Humidity	20% - 85% Non-Condensing

## Mounting

Wall Mount	✔ VESA 100x100mm
Flush Mount	✔ Mounting Strips Included
Stand	✔ Adjustable and Detachable

## Certifications & Standards

Certifications	CE, FCC, RoHS, REACH, WEEE, IC, C-Tick, UKCA, e-Mark, EN50155, EN60601-1, EN60601-1-2, CCC
----------------	--

## Package Content

Includes	Monitor, Stand, Remote Control, Mounting Strips, AC Power Adapter, Manual
----------	---

## Compatible Accessories

Dimmer	<a href="#">Compatible With External Dimmer (DMK7/DMK8)</a>
Wall Mounting	<a href="#">Compatible With Flat Wall Mount Bracket (VWB1)</a>
Stand	<a href="#">Compatible With VDK7 Metal Stand</a>



