




Model: 15SDI7M

15 Inch Monitor Metal SDI

This 15 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 15 inch monitor has a sturdy metal housing and is ideal for desktop, flush and wall mounting. The 15SDI7M can be easily connected to multiple HDMI, and SDI sources as well as daisy chained to other screens thanks to the inputs and outputs available.

- ✓ 1920 x 1080 resolution (Full HD)
- ✓ Input: HDMI (input & output), SDI (2x input & 2x output)
- ✓ Mounting: Flush, embedded, wall, desktop
- ✓ External dimensions: 15.2 x 9.5 x 1.6 inches



General

Manufacturer	Beetronics
Item number	15SDI7M
Product name	15 Inch Monitor Metal SDI
Warranty	2 years
User Manual	Download PDF
Quickstart	Download PDF

Panel

Diagonal size	15.6 inches (396 mm)
Panel type	IPS-LCD
Aspect ratio	16:9 (4:3 adjustable)
Response time	10 ms
MTBF	50K
Native resolution	1920 x 1080
Supported resolutions	1920 x 1080 (max), 640 x 480 (min)
Pixels per inch	146 PPI
Backlight	LED
Brightness	350 cd/m ²
Contrast	700:1
Color encoding system	PAL/NTSC/SECAM
Viewing angle	178° horizontal, 178° vertical

Connectivity

HDMI input	1x
HDMI output	1x
AUX input	1x
AUX output	1x
USB-A	1x integrated USB media player
SDI input (3G)	2x
SDI output	2x

Size & weight

Color	Black
Weight	5.3 lbs (7.0 lbs with stand)
Width	15.1 inches
Height	9.4 inches
Thickness	1.6 inches
Display dimensions	13.5 x 7.7 inches

Features and functions

Audio	Integrated speakers
Key-lock	The control buttons can be blocked
Auto-on	Automatically powers on when it receives current or a signal
Dimmable	Adjustable backlight brightness
Mirroring	Image can be mirrored, horizontally and vertically
Orientation	Landscape, portrait, face-up
USB media player	The monitor is equipped with a built-in USB media player.

Power

Input voltage	DC 9-33V
Consumption	22.3 Watt
Power adapter	Input: AC100-240V, 50/60Hz , Output: 12V-3A

Environmental

Max. non-stop operating time	24/7
Operating temperature	-4°F to +140°F
Storage temperature	-4°F to +158°F
Operating humidity	20% - 80% non-condensing

Mounting

Wall mount	✔ VESA (75 mm)
Flush mount	✔ Mounting strips included
Stand	✔ Adjustable and detachable

Certifications & Standards

Certifications	CE, FCC, RoHS, REACH, WEEE, IC, UKCA, e-Mark, EN50155, CCC
----------------	--

Package content

Includes	Monitor, Stand, Remote control, Mounting strips, AC power adapter, Manual
----------	---

Compatible accessories

Dimmer	Compatible with external dimmer (DMK7/DMK8)
Rack mounting	Compatible with 19 inch rack mount kit (RMK2)
Wall mounting	Compatible with flat wall mount bracket (VWB1)



15SDI

