





Model: 19HB9M

19 Inch Touchscreen Metal (High Brightness)

- ✓ High brightness full HD multi-touch panel
- ✓ Input: HDMI, DisplayPort, USB-C, VGA
- ✓ Mounting: Flush, embedded, panel mount
- ✓ External dimensions: 18.6 x 11.7 x 1.7 inches



General

Manufacturer	Beetronics
Item number	19HB9M
Product name	19 Inch Touchscreen Metal (High Brightness)
Warranty	2 years
User Manual	Download PDF
Quickstart	Download PDF

Supported operating systems

Windows	Windows 8, 10, 11
Windows Embedded	Windows Embedded 8 Industry, 8.1 Industry, IoT Enterprise
macOS	Big Sur, Monterey, Ventura, Sonoma
Linux	All Linux distributions
ChromeOS	All ChromeOS versions
Brightsign	All BrightsignOS versions

Panel

Diagonal size	18.7 inches (475 mm)
Aspect ratio	16:9 (4:3 adjustable)
Native resolution	1920 x 1080
Supported resolutions	1920 x 1080 (max), 640 x 480 (min)
Pixels per inch	118 PPI
Brightness	1000 nits
Contrast	1000:1
Color encoding system	PAL/NTSC/SECAM
Viewing angle	170° horizontal, 170° vertical
Touch technology	Capacitive, 10-point multi-touch (PCAP), optically bonded
Touch Control	Stylus, hand, glove

Connectivity

HDMI	1x
DisplayPort	1x
VGA	1x
AUX input	1x
AUX output	1x
USB-C	1x Video, Audio, Touch
USB-A	Via USB-C to USB-A adapter. This only activates the touch functionality and should be combined with HDMI, the DisplayPort, or VGA for image display.

Size & weight

Color	Black
Width	18.6 inches
Height	11.7 inches
Thickness	1.7 inches
Display dimensions	16.3 x 9.2 inches

Features and functions

Key-lock	The control buttons can be blocked
Auto-on	Automatically powers on when it receives current or a signal
Dimmable	Automatic dimming based on ambient light via an integrated light sensor. Manual dimming via the remote control or an optional dimmer knob.

Power

Input voltage	DC 10-36V
Consumption	18.2 Watt
Power adapter	Input: AC100-240V, 50/60Hz , Output: 19V-1.5A

Environmental

Operating temperature	-4°F to +140°F
Storage temperature	-4°F to +158°F
Operating humidity	20% - 80% non-condensing

Mounting

Wall mount	<input checked="" type="checkbox"/> VESA (100 mm)
Flush mount	<input checked="" type="checkbox"/> Panel mount accessories included.

Certifications & Standards

IP rating	IP65 front panel, IP65 when panel mounted
Certifications	CE, FCC, RoHS, REACH, WEEE, IC, UKCA, e-Mark, EN50155, CCC

Package content

Includes	Package includes: Touchscreen, USB-C to USB-C cable, USB-C to USB-A cable, remote control, mounting clamps (8x), mounting strips (8x), screws (8x), rubber seal, power adapter, and manual.
----------	---

Compatible accessories

Dimmer	Compatible with external dimmer (DMK7/DMK8)
Wall mounting	Compatible with flat wall mount bracket (VWB1)
Touch Pen	Compatible with CTS7 capacitive touchscreen stylus



15HB9M

