



## 7 inch touchscreen metal

Model: 7TS7M

This high resolution 7 inch touchscreen has a reliable multi-touch panel which ensures accurate operation. The 7TS7M delivers best-in-class picture quality with excellent 178° viewing angles and is compatible with Windows, Mac, Linux & Android operating systems. The touchscreen monitor is designed for professional applications, easy to integrate and suitable for intensive use.

- ✓ High resolution multi-touch panel
- ✓ Windows, Mac, Linux & Android compatible
- ✓ Desktop, flush and wall mountable
- ✓ 7.1 x 4.8 x 1.5 inches



#### GENERAL

Manufacturer	Beetronics
Item number	7TS7M
Previous model	7TS4M
Product name	7 inch touchscreen metal
Warranty	2 years
Drivers	[ <a href="#">driversLink</a> ]

#### SUPPORTED OPERATING SYSTEMS

Windows	Windows 8, 10, 11
Windows Embedded	Windows Embedded 8 Industry, Windows Embedded 8.1 Industry, Windows IoT Enterprise
macOS	Catalina, Big Sur, Monterey
Linux	All Linux distributions
Chrome OS	All ChromeOS versions
Brightsign	All BrightsignOS versions
Android	Android 8.0 and higher - not compatible with smartphones or tablets

#### PANEL

Type	LED-IPS
Diagonal size	7 inches (183 mm)
Aspect ratio	16:10 (16:9, 4:3 adjustable)
Native resolution	1280 x 800
Supported resolutions	1920 x 1200 (max), 640 x 480 (min)
Pixels per inch	215 PPI
Viewing angle	178° horizontal, 178° vertical
Brightness	350 cd/m2
Contrast	800:1
Touch technology	Capacitive, 10-point multitouch (PCAP)
Control	Stylus, hand, glove

#### CONNECTIVITY

HDMI	✓ 1x
VGA	✓ 1x
BNC (CVBS)	✓ 1x
RCA video	✓ 1x
AUX input	✓ 1x
AUX output	✓ 1x
USB	✓ Only for touchscreen functionality

**SIZE & WEIGHT**

Colour	Black
Weight	1,5 lbs (2 lbs with stand)
Width	7.1 inches
Height	4.8 inches (+0 to 1.5 inches with stand)
Thickness	1.5 inches
Display dimensions	5.9 x 3.7 inches

**FEATURES AND FUNCTIONS**

Audio	Integrated speakers
Key-lock	The control buttons can be blocked
Auto-on	Automatically powers on when it receives current or a signal
Dimmable	Adjustable backlight brightness
Mirroring	Image can be mirrored, horizontally and vertically

**POWER**

Input voltage	DC 9-28V
Power supply	Input: 110-240V ~ 50/60Hz - Output: 12V-2A
Consumption	5.4 Watt

#### ENVIRONMENTAL

Operating temperature	-4°F to +140°F
Storage temperature	-4°F to +158°F
Operating humidity	20% - 90% non-condensing

#### MOUNTING

Wall mount	✓ VESA (75 mm)
Flush mount	✓ Mounting strips included
Stand	✓ Adjustable and detachable

#### CERTIFICATIONS & STANDARDS

IP rating	IP65 front panel
Certifications	CE, FCC, RoHS, REACH, UKCA

#### PACKAGE CONTENT

Includes	Touchscreen, USB cable, Remote control, AC power adapter, Stand, Installation strips, Manual
----------	--



