



Model: 15TSV7M

15 Inch Touchscreen Metal (4:3)

This 15 inch touchscreen has a reliable multi-touch panel with a 4:3 aspect ratio. The monitor delivers excellent 178° viewing angles and is compatible with Windows, Mac & Linux operating systems. The touchscreen monitor is designed for professional applications, easy to integrate and suitable for intensive use.

- ✓ 4:3 multi-touch panel
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Flush, embedded, wall, desktop
- ✓ External dimensions: 13.6 x 10.6 x 1.9 inches



General

Manufacturer	Beetronics
Item number	15TSV7M
Previous model	15TSM
Product name	15 Inch Touchscreen Metal (4:3)
Warranty	2 years
User Manual	Download PDF
Quickstart	Download PDF

Supported operating systems

Windows	Windows 8, 10, 11
Windows Embedded	Windows Embedded 8 Industry, 8.1 Industry, IoT Enterprise
macOS	Big Sur, Monterey, Ventura, Sonoma
Linux	All Linux distributions
ChromeOS	All ChromeOS versions
Brightsign	All BrightsignOS versions

Panel

Diagonal size	15.0 inches (381 mm)
Panel type	IPS-LCD
Aspect ratio	4:3
Response time	10 ms
MTBF	50K
Native resolution	1024 x 768
Supported resolutions	1920 x 1080 (max), 640 x 480 (min)
Pixels per inch	85 PPI
Backlight	LED
Brightness	350 cd/m2
Contrast	1500:1
Color encoding system	PAL/NTSC/SECAM
Viewing angle	178° horizontal, 178° vertical
Surface	Mat tempered glas
Touch technology	Capacitive, 10-point multitouch (PCAP)
Touch Control	Stylus, hand, glove

Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA video	1x
AUX input	1x
AUX output	1x
USB-A	Only for touchscreen functionality

Size & weight

Color	Black
Weight	6.6 lbs (7.9 lbs with stand)
Width	9.5 inches
Height	10.6 inches
Thickness	1.8 inches
Display dimensions	12.0 x 9.0 inches

Features and functions

Audio	Integrated speakers
Key-lock	The control buttons can be blocked
Auto-on	Automatically powers on when it receives current or a signal
Dimmable	Adjustable backlight brightness
Mirroring	Image can be mirrored, horizontally and vertically
Orientation	Landscape, portrait, face-up

Power

Input voltage	DC 9-33V
Consumption	Power consumption (typical): 11.8 W (on), 0.4 W (standby)
Power supply	External DC (power adapter included)
Power adapter	Input: AC100-240V, 50/60Hz , Output: 12V-3A
Power adapter output connector	DC barrel plug 2.1mm x 5.5mm

Environmental

Max. non-stop operating time	24/7
Operating temperature	-4°F to +140°F
Storage temperature	-4°F to +158°F
Operating humidity	20% - 80% non-condensing

Mounting

Wall mount	<input checked="" type="checkbox"/> VESA (75 mm)
Flush mount	<input checked="" type="checkbox"/> Mounting strips included
Stand	<input checked="" type="checkbox"/> Adjustable and detachable

Certifications & Standards

IP rating	IP65 front panel
Impact protection	IK07
Certifications	CE, FCC, RoHS, REACH, WEEE, IC, UKCA, e-Mark, EN50155, EN60601, CCC

Package content

Includes	Touchscreen, USB cable, Remote control, AC power adapter, Stand, Installation strips, Manual
----------	--

Compatible accessories

Stand

Compatible with VDK3 collapsible stand

Touch Pen

Compatible with CTS7 capacitive touchscreen stylus



